

Technical drawing of a rectangular building plan. The overall dimensions are 1777 cm by 1600 cm. The drawing shows a grid of columns and beams. Key features include:

- Dimensions:** 1777 cm (width) and 1600 cm (depth).
- Column Spacing:** 200/225 cm (horizontal) and 200/225 cm (vertical).
- Column Labels:** #10/20 cm, #12/20 cm, #14/20 cm, #16/20 cm, #18/20 cm, #20/20 cm.
- Beam Labels:** #10/20 cm, #12/20 cm, #14/20 cm, #16/20 cm, #18/20 cm, #20/20 cm.
- Diagonal Lines:** Two diagonal lines crossing the plan, labeled "AB" and "CD".
- Structural Details:** A section labeled "AB" is shown on the left, and a section labeled "CD" is shown on the right. The section "AB" is labeled "AB 10/20 cm" and "10/20 cm". The section "CD" is labeled "CD 10/20 cm" and "10/20 cm".
- Orientation:** The drawing is oriented with a North arrow pointing towards the top right.

[illegible]

Technical drawing showing three cross-sections of a bridge structure, labeled A-A, B-B, and C-C.

Section A-A: A trapezoidal pier with a height of 20m and a base width of 3.26m. The top width is 1.0/1.0m. The pier is shown with a cross-hatched pattern and a central vertical axis.

Section B-B: A rectangular pier with a height of 30m and a base width of 3.26m. The pier is shown with a cross-hatched pattern and a central vertical axis.

Section C-C: A rectangular pier with a height of 30m and a base width of 3.16m. The pier is shown with a cross-hatched pattern and a central vertical axis.

Labels for each section include: **PREREZ A-A**, **PREREZ B-B**, and **PREREZ C-C**. The drawing also includes dimensions for the height (20, 30) and base width (3.26, 3.16) of the piers, and the top width (1.0/1.0) for section A-A.

[illegible]

ARMATURNI NAČRT POZ. 20
M 1:50

PREREZ A
M 1:1.25

ELEMENT - PRITULJE			
Poz	Kon	Dim	L. [m]
1	14,4	14	6,0
15	90	14	2,44

Tablica armiranja (schematski)

Technical drawing of a vertical post (Prituliče) with a cross-section diagram. The post has a total height of 373 and a diameter of 30. The cross-section is a square with a diagonal of 30 and a side length of 30. The post is divided into three sections: 144 (top), 90 (middle), and 90 (bottom). The cross-section is labeled with dimensions 144, 90, and 90. The cross-section is labeled with dimensions 144, 90, and 90.

Red	Kom	Sex	L (m)	Oblik križaljke (oboznačeno)	Školska težina mg	Školska reža (mg)
1	144	14	6,0	600	864,0	1.073,08
15	90	14	6,0	110	219,60	272,74
16	116	14	4,54	354	526,64	654,09
17	912	8	1,06	24	66,72	391,52
18	56	14	4,43	443	248,08	308,11
19	120	8	1,06	24	127,20	51,52
20	701	10	1,54	14	1.079,54	684,43
21	6	16	9,54	94	57,24	92,19
22	6	10	6,0	600	36,0	27,82
23	61	10	2,44	24	14,84	94,31
24	6	12	3,50	350	21,0	19,17
25	21	10	1,02	19	214,2	13,58
26	6	16	6,0	50	36,0	58,36
27	3	14	6,0	600	80,0	22,36
28	80	10	1,42	24	113,60	72,02
29	6	12	2,82	282	16,2	15,41
30	19	8	0,86	14	16,34	6,62
31	7	16	6,60	600	44,20	74,89
32	3	14	6,0	600	80,0	22,36
33	6	16	7,84	600	47,84	76,25
34	3	16	6,0	784	80,0	29,98
35	4	14	7,24	49	28,96	35,97
36	49	10	1,62	24	79,38	50,33
37	49	10	2,0	200	98,0	62,18
38	6	16	10,30	970	61,80	100,13
39	3	16	9,0	900	67,0	43,77
40	7	14	9,70	970	73,0	84,33
41	65	10	2,12	74	137,80	87,37
42	8	14	4,40	24	35,20	43,72
43	24	10	1,16	24	27,84	17,65
44	4	14	2,96	146	11,84	16,70
45	3	12	2,06	146	6,18	5,63
46	8	10	1,12	24	8,96	5,68
47	56	428	10	24	349,4	595,37
48	57	169	12	24	338,0	307,92
49	58	27	12	300	810	73,19
50	16	12	3,0	300	4,80	43,73
60	1100	8	0,86	20	944,0	383,13

Premer	Dolžina po premeru		Težina po premeru	
16 mm	291,28		2,531,47 kg	
18 mm	2.038,22 m		190,21 kg	
20 mm	217,22		161,21 kg	
10 mm	2.230,74 m		1.416,29 kg	
8 mm	2.056,26 m		832,78 kg	
SKUPAJ			5.446,26 kg	
do 412 mm	2.429,38 kg			
nad 412 mm	3.006,88 kg			

Pozicija	Tip	Št.	Število	Dolžina	Širina	Masa
1	0257	52		600 cm	220 cm	2.860,0 kg
2	0335	52		600 cm	220 cm	3.744,00 kg
Skupaj						6.604,0 kg

[illegible]

M 1:50

The diagram shows a cross-section of a bridge with a single-track railway track. The track has a height of 155 cm from the base to the top of the rail bed. The total width of the bridge deck is 670 cm. The track is supported by a central pier and two side piers. The distance between the centerlines of the tracks is 30 cm. The elevation at the right end is +2.91 m above sea level.

Opaž na sredini razpoja nadvišati za 250 cm !

[illegible]

Projektant: projektat			
VPR VPR GREGA URATNIK S.p. Cesta v Ranča 12 2313 Fram Projektiranje gradbenih konstrukcij in tehnično svetovanje			
Opisno redna zaveza	Ime in priimek	ID številka	Priimek
	Mojca Kraljevac u.d.a.	A 0476	
Opisno projektat	Grega Uratnik d.l.g.	G 3958	
Projektat	Grega Uratnik d.l.g.	G 3958	
Ime projekta		Številka naloga	
PZI		41/9/2017	

naslov	OBČINA SLOVENSKA BISTRICA Kolodvorska 10 2310 Slovenska Bistrica		
opis	NOV VRTEC V OŽKI ULICI		
zadev	ARMATURNI NAČRT POZ 201 - 211		
vrsta zadeve	3 - GRADBENE KONSTRUKCIJE		
rednosta	150, 112,5	datum	november 2011
predmet			2.